

Source File: ~/2336/27/lab27.cpp
Input: under control of main function
Output: under control of main function
Value: 2

The purpose of this assignment is to perform some vector processing. Three different versions of the same function template are to be written, one using indexing, one using iterators, and one using pointers. The prototypes can be found in the main function shown below. The function templates receive as input a vector. Each function returns the mode of the elements and the number of occurrences of the mode. The mode is defined as the value which occurs most frequently in a set of data. Each function should utilize the solution strategy of sorting the incoming vector in ascending order (use the built-in sort algorithm to accomplish this) and then using a single linear loop to determine the mode. The running time of each of your functions must be $O(N \log N)$, where N represents the size of the incoming vector.

A sample main function for testing your functions is shown in Figure 1. Commands to compile, link, and run this assignment are shown in Figure 2. To use the Makefile as distributed in class, add a target of lab27main to targets1srcfile.

```

1 #include <iostream>
2 #include <cstdlib>
3 #include <vector>
4 #include <utility>
5 #include <string>
6
7 using namespace std;
8
9 template<typename T>
10 pair<T, int> modeUsingIndexing(const vector<T>& v);
11
12 template<typename T>
13 pair<T, int> modeUsingIterators(const vector<T>& v);
14
15 template<typename T>
16 pair<T, int> modeUsingPointers(const vector<T>& v);
17
18 #include "lab27.cpp"
19
20 template<typename T>
21 void callModeFunctions(const vector<T>& v, string nameOfVector)
22 {
23     if (v.size() == 0)
24         cout << "No data\n";
25     else
26     {
27         cout << "For vector " << nameOfVector << ":" << endl;
28         pair<T, int> result = modeUsingIndexing(v);
29         cout << " Using Indexing Mode = " << result.first
30             << " # of occurrences = " << result.second << endl;
31 }
```

Figure 1. /usr/local/2336/src/lab27main.C (Part 1 of 2)

```
32     result = modeUsingIterators(v);
33     cout << "Using Iterators Mode = " << result.first
34         << "# of occurrences = " << result.second << endl;
35
36     result = modeUsingPointers(v);
37     cout << " Using Pointers Mode = " << result.first
38         << "# of occurrences = " << result.second << endl;
39     cout << endl;
40 }
41 }
42
43 int main()
44 {
45     const int aCount = 5, bCount = 1, cCount = 14, dCount = 12;
46     int a[aCount] = {5, 5, 5, 5, 5};
47     double b[bCount] = {7.7};
48     char c[cCount] = {'r', 'a', 'c', 'e', 'c', 'a', 'r',
49                       ' ', 'd', 'r', 'i', 'v', 'e', 'r'};
50     string d[dCount] = {"Cadillac", "GMC", "GMC",
51                         "Lexus", "Lexus", "Dodge", "GMC", "BMW",
52                         "BMW", "GMC", "Dodge", "Lexus"};
53
54     vector<int> aVector(a, a + sizeof(a) / sizeof(a[0]));
55     callModeFunctions(aVector, "aVector");
56
57     vector<double> bVector(b, b + sizeof(b) / sizeof(b[0]));
58     callModeFunctions(bVector, "bVector");
59
60     vector<char> cVector(c, c + sizeof(c) / sizeof(c[0]));
61     callModeFunctions(cVector, "cVector");
62
63     vector<string> dVector(d, d + sizeof(d) / sizeof(d[0]));
64     callModeFunctions(dVector, "dVector");
65
66     int num;
67     vector<int> v;
68
69     while (cin >> num)
70         v.push_back(num);
71
72     callModeFunctions(v, "v");
73
74     return EXIT_SUCCESS;
75 }
```

Figure 1. /usr/local/2336/src/lab27main.C (Part 2 of 2)

```
1 newuser@csunix ~> cd 2336
2 newuser@csunix ~/2336> ./getlab.ksh 27
3   * Checking to see if a folder exists for Lab 27. . .No
4   * Creating a folder for Lab 27
5   * Checking to see if Lab 27 has sample input and output files. . .Yes
6   * Copying input and output files for Lab 27
7     from folder /usr/local/2336/data/27 to folder ./27
8   * Checking to see if /usr/local/2336/src/lab27main.C exists. . .Yes
9   * Copying file /usr/local/2336/src/lab27main.C to folder ./27
10  * Checking to see if /usr/local/2336/include/lab27.h exists. . .No
11  * Copying file /usr/local/2336/src/Makefile to folder ./27
12  * Adding a target of lab27main to targets1srcfile
13  * Touching file ./27/lab27.cpp
14  * Edit file ./27/lab27.cpp in Notepad++
15 newuser@csunix ~/2336> cd 27
16 newuser@csunix ~/2336/27> ls
17 01.dat          02.out        10.dat        lab27.cpp
18 01.out          03.dat        10.out        lab27main.C
19 02.dat          03.out        Makefile
20 newuser@csunix ~/2336/27> make lab27main
21 g++ -g -Wall -std=c++11 -c lab27main.C -I/usr/local/2336/include -I.
22 g++ -o lab27main lab27main.o -L/usr/local/2336/lib -lm -lbits
23 newuser@csunix ~/2336/27> cat 01.dat
24 6 2 6
25 newuser@csunix ~/2336/27> cat 01.dat | ./lab27main
26 For vector aVector:
27   Using Indexing Mode = 5 # of occurrences = 5
28   Using Iterators Mode = 5 # of occurrences = 5
29   Using Pointers Mode = 5 # of occurrences = 5
30
31 For vector bVector:
32   Using Indexing Mode = 7.7 # of occurrences = 1
33   Using Iterators Mode = 7.7 # of occurrences = 1
34   Using Pointers Mode = 7.7 # of occurrences = 1
35
36 For vector cVector:
37   Using Indexing Mode = r # of occurrences = 4
38   Using Iterators Mode = r # of occurrences = 4
39   Using Pointers Mode = r # of occurrences = 4
40
41 For vector dVector:
42   Using Indexing Mode = GMC # of occurrences = 4
43   Using Iterators Mode = GMC # of occurrences = 4
44   Using Pointers Mode = GMC # of occurrences = 4
45
46 For vector v:
47   Using Indexing Mode = 6 # of occurrences = 2
48   Using Iterators Mode = 6 # of occurrences = 2
49   Using Pointers Mode = 6 # of occurrences = 2
```

Figure 2. Commands to Compile, Link, & Run Lab 27 (Part 1 of 2)

```
50  
51 newuser@csunix ~/2336/27> cat 01.dat | ./lab27main > my.out  
52 newuser@csunix ~/2336/27> diff 01.out my.out  
53 newuser@csunix ~/2336/27> cat 02.dat | ./lab27main > my.out  
54 newuser@csunix ~/2336/27> diff 02.out my.out  
55 newuser@csunix ~/2336/27> cat 03.dat | ./lab27main > my.out  
56 newuser@csunix ~/2336/27> diff 03.out my.out  
57 newuser@csunix ~/2336/27> cat 10.dat | ./lab27main > my.out  
58 newuser@csunix ~/2336/27> diff 10.out my.out  
59 newuser@csunix ~/2336/27>
```

Figure 2. Commands to Compile, Link, & Run Lab 27 (Part 2 of 2)